


Arrive EyePoint™

UPTZ HD Video Conferencing Camera
Model AEP-PTZ-3030



The Arrive EyePoint™ 3030 HD-PTZ Video Conferencing Camera comes from the Arrive EyePoint™ family of USB 3.0 super-speed HD cameras and sports an efficient image sensor. It offers unparalleled clarity and resolution for a host of applications, irrespective of room sizes and light conditions. It is an ideal solution for video conferencing, distance learning, training, meeting, courtroom and any other application that requires a small form factor camera with a wide angle, zoom lens. You can directly plug the AEP-3030 camera into your PC without the need for a separate capture device. Because the AEP-3030 camera uses standard USB Video Class (UVC) drivers, no special USB drivers need to be installed. As a result they work seamlessly with any software application running on any OS that supports USB 3.0 devices.

The camera features a 10X optical zoom lens with a 49 degree angle of view. The zoom range provides great flexibility for a wide variety of applications.



AEP-PTZ-3030



Key Features

- ⦿ Outputs Super Speed USB 3.0 video direct to Arrive Edgeless Media® Processors or compatible PCs with USB 3.0 ports.
- ⦿ Uses standard UVC drivers for USB 3.0
- ⦿ 1/3 type high-speed CMOS Image Sensor
- ⦿ 2.1 Megapixels
- ⦿ 10X optical zoom lens
- ⦿ Low 0.1 lux illumination operation capability
- ⦿ Smooth Pan and Tilt Motor with high response rates and 64 Preset position capabilities.



Hardware

Display

Aspect ratio	16:9
Video Format /Resolution	YuY2 1920 X 1080 @ 30fps, 1280 X 720 @ 60fps High Quality Image Resolution optimized for Video Conferencing
Frame rate (typical)	30 Frames per second
Field of View	51.8°
Signal to Noise ratio (minimum)	>50db

Image Sensor

Sensor	1/3" highly efficient primary color CMOS, 2.1M compatible
Minimum illumination	0.1 lux at F2.0
White balance	Auto / Manual
Gain control	Auto
Backlight compensation	On/Off
Electronic shutter	1/30 ~ 1/10,000 s


Optical Lens

Lens	10X Optical ZOOM 1/3.6 model f=5 - 50.0mm F2.0 - 2.8
Iris	Auto / Manual
Focus	Auto
Pixel Element	2.1 Megapixels

Camera Specifications

Video Output	USB 3.0
	Easy to install using the UVC standard drivers for USB 3.0 video, the HD-USB camera is an easy to install PTZ camera for Unified Communications soft client conferencing systems such as Skype®, Google+®, Jabber®, Lync® and more.
Communication	EIA / RS-232 (Bi-directional)
PTZ Control Protocol	VISCA, PELCO-D
Baud Rate	4800/9600 bps
Preset	64
Save status after Power off	Supported
Speed Matching Function	Supported
OSD Menu	Supported
Image Auto Flip	Supported
Pan Speed	0-100°
Tilt Speed	0-80°
Pan Rotation Angle	359°
Tilt Rotation Angle	UP: 90°, Down: 45°
Auto Pan Scan	Supported
Boundary Scan	0-359° (Programmable)

Rear Panel Ports



- | | |
|--|---|
| 1. USB 3.0 interface | A super speed transfer interface |
| 2. IR Receiver | Sensor to receive IR remote controller signal |
| 3. VISCA IN/RS232;
VISCA OUT/RS485
Control Interface | Accommodates daisy chain connection of multiple cameras. When multiple cameras are connected to PC via RS-232C (VISCA IN), connect VISCA OUT of the first camera to VISCA IN of the second camera |
| 4. DC 12V 1.2A | Power supply socket |

Included Cables and Accessories

- Standard AC-DC Power Adapter
- VISCA control connection cable to 2-PIN phoenix
- Infrared remote (2 X AAA batteries excluded)
- VISCA to DB9 cable
- USB 3.0 Cable
- Standard tripod adapter puck

Mounting


Desktop, Ceiling / Wall mount, Standard tripod using adapter puck supplied with the packaging.

SPECIFICATIONS

Arrive EyePoint™ 3030-UPTZ HD Video Conferencing Camera

Model AEP-PTZ-3030

Dimensions and Weight



Unit Dimension	4.9"W X 4.7" H X 5.9"D (124 X 121 X 150.7mm)
Shipping dimensions (4 units/box)	18.110"W X 9.842"H X 14.960"D (460 X 250 X 380mm)
Net Weight/unit	1.433 lb (650 grams)
Gross Shipping weight (4 units/box)	15.432 lb (7.0 kg)

Storage and operating requirements

Power requirements	DC12V ±10% 1.2A
Operative Temperature	14° to 140° F (-10° to 60° C)
Environmental Humidity	0-95% Relative Humidity (non-condensation)

Certification and compliance

Regulatory certification	FCC Class A, CE
Environmental compliance	RoHS, WEEE

Purchasing information

Model No	AEP-PTZ-3030
Description	Arrive EyePoint™ 3030 UPTZ HD Video Conferencing Camera
SKU#	AEP-3030-001-001
Warranty Information	All Arrive Peripherals ship with a standard limited 12 months first user warranty. Please refer to Ver. SLHW-P-0101-15 - visit carepoint.arrivesys.com/warranty for updated information on warranty.



Arrive Systems, Inc.
6737 Katella Avenue
Cypress, CA 90630, USA
info@arrivesys.com
+1-888-502-0715 (USA/Canada Toll Free)



AEP-3030-803-002

Copyright © 2015 Arrive Systems, Inc. All rights reserved. All trademarks and copyrights, whether acknowledged or otherwise, are owned by their respective owners. Arrive® does not claim ownership of any trademark other than the Arrive®, Arrive InfoPoint™, Arrive RoomPoint™, Arrive FacePoint™, Arrive ViewPoint™, Arrive CloudPoint™, Arrive MediaPoint™, Arrive AirPoint™, Arrive NetPoint™, Arrive TouchPoint™, Arrive ControlPoint™, Arrive CablePoint™, Arrive EyePoint™, Arrive VoicePoint™, Arrive SoundPoint™ and Arrive Edgeless Media® trademarks. Specifications are subject to change without notice. All images are provided for reference use only, are graphically generated and representative for promotional purposes. Finished goods, packaging and products will be provided with user interface designs and graphic elements including packaging design elements that may vary from the images shown in this document. E&OE.